

§ 27.59

must cease operations from the offending WCS facility.

(e) At least 30 days prior to commencing operations from any new WCS transmission site or with increased power from any existing WCS transmission site, a WCS licensee shall notify all BRS/EBS licensees in or through whose licensed service areas they intend to operate of the technical parameters of the WCS transmission facility. WCS and BRS/EBS licensees are expected to coordinate voluntarily and in good faith to avoid interference problems and to allow the greatest operational flexibility in each other's operations.

[62 FR 16498, Apr. 7, 1997, as amended at 69 FR 72034, Dec. 10, 2004]

§ 27.59 [Reserved]

§ 27.60 TV/DTV interference protection criteria.

Base, fixed, control, and mobile transmitters in the 698–764 MHz and 776–794 MHz frequency bands must be operated only in accordance with the rules in this section to reduce the potential for interference to public reception of the signals of existing TV and DTV broadcast stations transmitting on TV Channels 51 through 68.

(a) *D/U ratios.* Licensees must choose site locations that are a sufficient distance from co-channel and adjacent channel TV and DTV stations, and/or must use reduced transmitting power or transmitting antenna height such that the following minimum desired signal-to-undesired signal ratios (D/U ratios) are met.

(1) The minimum D/U ratio for co-channel stations is:

(i) 40 dB at the hypothetical Grade B contour (64 dB μ V/m) (88.5 kilometers (55 miles)) of the TV station;

(ii) For transmitters operating in the 698–746 MHz frequency band, 23 dB at the equivalent Grade B contour (41 dB μ V/m) (88.5 kilometers (55 miles)) of the DTV station; or

(iii) For transmitters operating in the 746–764 MHz and 776–794 MHz frequency bands, 17 dB at the equivalent Grade B contour (41 dB μ V/m) (88.5 kilometers (55 miles)) of the DTV station.

(2) The minimum D/U ratio for adjacent channel stations is 0 dB at the hy-

47 CFR Ch. I (10–1–05 Edition)

pothetical Grade B contour (64 dB μ V/m) (88.5 kilometers (55 miles)) of the TV station or –23 dB at the equivalent Grade B contour (41 dB μ V/m) (88.5 kilometers (55 miles)) of the DTV station.

(b) *TV stations and calculation of contours.* The methods used to calculate TV contours and antenna heights above average terrain are given in §§ 73.683 and 73.684 of this chapter. Tables to determine the necessary minimum distance from the 698–764 MHz or 776–794 MHz station to the TV/DTV station, assuming that the TV/DTV station has a hypothetical or equivalent Grade B contour of 88.5 kilometers (55 miles), are located in § 90.309 of this chapter and labeled as Tables B, D, and E. Values between those given in the tables may be determined by linear interpolation. Distances for station parameters greater than those indicated in the tables should be calculated in accordance with the required D/U ratios, as provided in paragraph (a) of this section. The locations of existing and proposed TV/DTV stations during the period of transition from analog to digital TV service are given in part 73 of this chapter and in the final proceedings of MM Docket No. 87–268.

(1) Licensees of stations operating within the ERP and HAAT limits of § 27.50 must select one of four methods to meet the TV/DTV protection requirements, subject to Commission approval:

(i) Utilize the geographic separation specified in Tables B, D, and E of § 90.309 of this chapter, as appropriate;

(ii) When station parameters are greater than those indicated in the tables, calculate geographic separation in accordance with the required D/U ratios, as provided in paragraph (a) of this section;

(iii) Submit an engineering study justifying the proposed separations based on the parameters of the land mobile station and the parameters, including authorized and/or applied for facilities, of the TV/DTV station(s) it is trying to protect; or,

(iv) Obtain written concurrence from the applicable TV/DTV station(s). If this method is chosen, a copy of the agreement must be submitted with the application.