

**Federal Communications Commission**

**§ 24.132**

(6) Three 100 kHz channels paired with 50 kHz channels:

- Channel 23: 940.55–940.65 and 901.45–901.50 MHz;
- Channel 24: 940.30–940.40 and 901.55–901.60 MHz; and
- Channel 25: 940.45–940.55 and 901.85–901.90 MHz.

(b) Five frequencies are available for assignment on a regional basis as follows:

(1) One 50 kHz channel paired with 50 kHz channel:

- Channel 12: 940.25–940.30 and 901.25–901.30 MHz.
- Channel 13: RESERVED.

(2) Four 50 kHz channels paired with 12.5 kHz channels:

- Channel 14: 930.55–930.60 and 901.7875–901.8000 MHz;
- Channel 15: 930.60–930.65 and 901.8000–901.8125 MHz;
- Channel 16: 930.65–930.70 and 901.8125–901.8250 MHz; and
- Channel 17: 930.70–930.75 and 901.8250–901.8375 MHz.

(c) Seven frequencies are available for assignment on an MTA basis as follows:

(1) Three 50 kHz unpaired channels:

- Channel 26: 901.35–901.40 MHz;
- Channel 27: 901.40–901.45 MHz; and
- Channel 28: 940.40–940.45 MHz.

(2) One 50 kHz channel paired with 50 kHz channel:

- Channel 29: 930.80–930.85 and 901.95–902.00 MHz.

(3) One 100 kHz channel paired with 50 kHz channel:

- Channel 30: 930.30–930.40 and 901.65–901.70 MHz.

(4) One 150 kHz channel paired with 50 kHz channel:

- Channel 31: 930.85–931.00 and 901.7–901.75 MHz.

(5) One 100 kHz channel paired with 12.5 kHz channel:

- Channel 32: 940.90–941 and 901.8375–901.85 MHz.

NOTE TO § 24.129: Operations in markets or portions of markets which border other countries, such as Canada and Mexico, will be subject to on-going coordination arrangements with neighboring countries.

[66 FR 29920, June 4, 2001]

**§ 24.130 [Reserved]**

**§ 24.131 Authorized bandwidth.**

The authorized bandwidth of narrowband PCS channels will be 10 kHz for 12.5 kHz channels and 45 kHz for 50 kHz channels. For aggregated adjacent channels, a maximum authorized bandwidth of 5 kHz less than the total aggregated channel width is permitted.

**§ 24.132 Power and antenna height limits.**

(a) Stations transmitting in the 901–902 MHz band are limited to 7 watts e.r.p.

(b) Mobile stations transmitting in the 930–931 MHz and 940–941 MHz bands are limited to 7 watts e.r.p.

(c) Base stations transmitting in the 930–931 MHz and 940–941 MHz bands are limited to 3500 watts e.r.p. per authorized channel and are unlimited in antenna height except as provided in paragraph (d) of this section.

(d)(1) MTA and regional base stations located between 200 kilometers (124 miles) and 80 kilometers (50 miles) from their licensed service area border are limited to the power levels in the following table:

Antenna HAAT in meters (feet) (see § 24.53 for HAAT HAAT calculation method)	Effective radiated power (e.r.p.) (watts)
183 (600) and below .....	3500
183 (600) to 208 (682) .....	3500 to 2584
208 (682) to 236 (775) .....	2584 to 1883
236 (775) to 268 (880) .....	1883 to 1372
268 (880) to 305 (1000) .....	1372 to 1000
305 (1000) to 346 (1137) .....	1000 to 729
346 (1137) to 394 (1292) .....	729 to 531
394 (1292) to 447 (1468) .....	531 to 387
447 (1468) to 508 (1668) .....	387 to 282
508 (1668) to 578 (1895) .....	282 to 206
578 (1895) to 656 (2154) .....	206 to 150
656 (2154) to 746 (2447) .....	150 to 109
746 (2447) to 848 (2781) .....	109 to 80
848 (2781) to 963 (3160) .....	80 to 58
963 (3160) to 1094 (3590) .....	58 to 42
1094 (3590) to 1244 (4080) .....	42 to 31
1244 (4080) to 1413 (4636) .....	31 to 22
Above 1413 (4636) .....	16

(2) For heights between the values listed in the table, linear interpolation shall be used to determine maximum e.r.p.

(e) MTA and regional base stations located less than 80 kilometers (50 miles) from the licensed service area

### § 24.133

border must limit their effective radiated power in accordance with the following formula:

$$PW = 0.0175 \times dkm^* * 6.6666 \times hm^* * -3.1997$$

PW is effective radiated power in watts  
dkm is distance in kilometers  
hm is antenna HAAT in meters; see § 24.53 for HAAT calculation method

(f) All power levels specified in this section are expressed in terms of the maximum power, averaged over a 100 millisecond interval, when measured with instrumentation calibrated in terms of an rms-equivalent voltage with a resolution bandwidth equal to or greater than the authorized bandwidth.

(g) Additionally, PCS stations will be subject to any power limits imposed by international agreements.

[58 FR 59183, Nov. 8, 1993; 59 FR 15269, Mar. 31, 1994, as amended at 62 FR 27511, May 20, 1997; 65 FR 35853, June 6, 2000]

### § 24.133 Emission limits.

(a) The power of any emission shall be attenuated below the transmitter power (P), as measured in accordance with § 24.132(f), in accordance with the following schedule:

(1) For transmitters authorized a bandwidth greater than 10 kHz:

(i) On any frequency outside the authorized bandwidth and removed from the edge of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of up to and including 40 kHz: at least  $116 \text{ Log}_{10} ((f_d+10)/6.1)$  decibels or 50 plus  $10 \text{ Log}_{10} (P)$  decibels or 70 decibels, whichever is the lesser attenuation;

(ii) On any frequency outside the authorized bandwidth and removed from the edge of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 40 kHz: at least  $43+10 \text{ Log}_{10} (P)$  decibels or 80 decibels, whichever is the lesser attenuation.

(2) For transmitters authorized a bandwidth of 10 kHz:

(i) On any frequency outside the authorized bandwidth and removed from the edge of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of up to and including 20 kHz: at least  $116 \times \text{Log}_{10} ((f_d+5)/3.05)$  decibels or  $50+10 \times \text{Log}_{10} (P)$  decibels or 70 decibels, whichever is the lesser attenuation;

### 47 CFR Ch. I (10–1–09 Edition)

(ii) On any frequency outside the authorized bandwidth and removed from the edge of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 20 kHz: at least  $43+10 \text{ Log}_{10} (P)$  decibels or 80 decibels, whichever is the lesser attenuation.

(b) The measurements of emission power can be expressed in peak or average values provided they are expressed in the same parameters as the transmitter power.

(c) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

(d) The following minimum spectrum analyzer resolution bandwidth settings will be used: 300 Hz when showing compliance with paragraphs (a)(1)(i) and (a)(2)(i) of this section; and 30 kHz when showing compliance with paragraphs (a)(1)(ii) and (a)(2)(ii) of this section.

[58 FR 59183, Nov. 8, 1993. Redesignated at 59 FR 18499, April 19, 1994, as amended at 59 FR 14119, Mar. 25, 1994; 66 FR 10968, Feb. 21, 2001]

### § 24.134 Co-channel separation criteria.

The minimum co-channel separation distance between base stations in different service areas is 113 kilometers (70 miles). A co-channel separation distance is not required for the base stations of the same licensee or when the affected parties have agreed to other co-channel separation distances.

### § 24.135 Frequency stability.

(a) The frequency stability of the transmitter shall be maintained within  $\pm 0.0001$  percent ( $\pm 1$  ppm) of the center frequency over a temperature variation of  $-30^\circ$  Celsius to  $+50^\circ$  Celsius at normal supply voltage, and over a variation in the primary supply voltage of 85 percent to 115 percent of the rated supply voltage at a temperature of  $20^\circ$  Celsius.

(b) For battery operated equipment, the equipment tests shall be performed using a new battery without any further requirement to vary supply voltage.